

| EMPA of feldspar pairs, MAC-246: 01/24/17-01/25/17 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|------------------|-------------------------------|--------------------------------|--------------------|-------|-------------------|------------------|-------------------|-------------------|---------|-------|-------|-------|-------|-------|-------|-------|----------------|-------|-------|--------------------------|-------|-------|--------|---------|--------|--------|------------------------|
| 15 kV, 10 nA, 2µm spot | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| SAMPLE | Weight Percent | | | Atoms per 8 Oxygen | | | | | | | | | | | | | | Mole fractions | | | 2-Fsp T (Elkins & Grove) | | | | Comment | | | |
| | SiO ₂ | P ₂ O ₅ | Al ₂ O ₃ | FeO | CaO | Na ₂ O | K ₂ O | Rb ₂ O | Cs ₂ O | TOTAL | Si | P | Al | Fe | Ca | Na | K | Rb | Cs | Sum | xAb | xOr | xAn | T-Ab | | T-Or | T-An | T-Convg |
| Day-1 (01/24/17) | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Cold End (edge of segment-1) | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Cold End-PI1 | 69.328 | 0.440 | 20.322 | 0.013 | 0.168 | 9.780 | 0.929 | 0.260 | 0.013 | 101.254 | 2.984 | 0.016 | 1.031 | 0.000 | 0.008 | 0.816 | 0.051 | 0.007 | 0.000 | 4.914 | 0.933 | 0.058 | 0.009 | 543.01 | 544.75 | 544.75 | Failed | Avg=544.17 |
| Cold End-Kf1 | 62.881 | 0.342 | 18.873 | 0.048 | 0.010 | 2.895 | 12.244 | 0.463 | 0.000 | 97.758 | 2.948 | 0.014 | 1.043 | 0.002 | 0.001 | 0.263 | 0.732 | 0.014 | 0.000 | 5.015 | 0.264 | 0.735 | 0.001 | | | | | |
| Cold End-PI2 | 68.163 | 0.728 | 20.483 | 0.000 | 0.096 | 10.692 | 0.726 | 0.167 | 0.000 | 101.056 | 2.947 | 0.027 | 1.044 | 0.000 | 0.004 | 0.896 | 0.040 | 0.005 | 0.000 | 4.962 | 0.953 | 0.043 | 0.005 | 513.94 | 507.68 | 507.68 | 509.77 | |
| Cold End-Kf2 | 61.915 | 0.749 | 19.195 | 0.016 | 0.000 | 2.722 | 12.637 | 0.601 | 0.000 | 97.836 | 2.909 | 0.030 | 1.063 | 0.001 | 0.000 | 0.248 | 0.757 | 0.018 | 0.000 | 5.026 | 0.247 | 0.753 | 0.000 | | | | | |
| Cold End-PI3 | 67.835 | 0.906 | 20.719 | 0.000 | 0.194 | 10.338 | 0.903 | 0.237 | 0.027 | 101.160 | 2.932 | 0.033 | 1.055 | 0.000 | 0.009 | 0.866 | 0.050 | 0.007 | 0.001 | 4.952 | 0.936 | 0.054 | 0.010 | 495.82 | 495.82 | 495.82 | 495.82 | |
| Cold End-Kf3 | 60.626 | 0.673 | 19.051 | 0.002 | 0.000 | 2.427 | 12.508 | 0.637 | 0.035 | 95.959 | 2.906 | 0.027 | 1.076 | 0.000 | 0.000 | 0.226 | 0.765 | 0.020 | 0.001 | 5.020 | 0.228 | 0.772 | 0.000 | | | | | |
| Middle of Segment-1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| mid-Seg1 PI-1 | 66.989 | 0.462 | 19.785 | 0.001 | 0.122 | 10.586 | 0.681 | 0.221 | 0.025 | 98.872 | 2.963 | 0.017 | 1.032 | 0.000 | 0.006 | 0.908 | 0.038 | 0.006 | 0.000 | 4.971 | 0.954 | 0.040 | 0.006 | 546.53 | 529.54 | 546.53 | Failed | Avg=531.00 |
| mid-Seg1 Kf-1 | 61.651 | 0.383 | 18.464 | 0.025 | 0.013 | 2.935 | 11.978 | 0.369 | 0.000 | 95.818 | 2.946 | 0.016 | 1.040 | 0.001 | 0.001 | 0.272 | 0.730 | 0.011 | 0.000 | 5.017 | 0.271 | 0.728 | 0.001 | | | | | |
| mid-Seg1 PI-2 | 67.968 | 0.615 | 19.935 | 0.026 | 0.096 | 10.237 | 1.023 | 0.274 | 0.004 | 100.179 | 2.967 | 0.023 | 1.026 | 0.001 | 0.005 | 0.866 | 0.057 | 0.008 | 0.000 | 4.952 | 0.934 | 0.061 | 0.005 | 533.48 | 533.48 | 533.48 | 533.48 | |
| mid-Seg1 Kf-2 | 62.312 | 0.516 | 18.634 | 0.018 | 0.008 | 2.863 | 11.977 | 0.505 | 0.021 | 96.853 | 2.945 | 0.021 | 1.038 | 0.001 | 0.000 | 0.262 | 0.722 | 0.015 | 0.000 | 5.005 | 0.266 | 0.733 | 0.000 | | | | | |
| mid-Seg1 PI-3 | 64.764 | 0.346 | 19.972 | 0.071 | 0.074 | 10.501 | 1.292 | 0.230 | 0.004 | 97.256 | 2.931 | 0.013 | 1.065 | 0.003 | 0.004 | 0.921 | 0.075 | 0.007 | 0.000 | 5.018 | 0.922 | 0.075 | 0.004 | 526.69 | 526.69 | 526.69 | 526.69 | |
| mid-Seg1 PI-3 | 63.497 | 0.366 | 19.339 | 0.025 | 0.060 | 10.087 | 1.727 | 0.261 | 0.023 | 95.385 | 2.936 | 0.014 | 1.054 | 0.001 | 0.003 | 0.904 | 0.102 | 0.008 | 0.000 | 5.023 | 0.896 | 0.101 | 0.003 | 531.84 | 552.56 | 531.84 | 538.74 | |
| mid-Seg1 Kf-3 | 62.225 | 0.319 | 18.507 | 0.020 | 0.008 | 2.841 | 12.429 | 0.519 | 0.000 | 96.868 | 2.951 | 0.013 | 1.034 | 0.001 | 0.000 | 0.261 | 0.752 | 0.016 | 0.000 | 5.028 | 0.258 | 0.742 | 0.000 | | | | | |
| Middle of Segment-2 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| mid-Seg2 PI-1 | 66.091 | 0.547 | 19.929 | 0.035 | 0.097 | 10.705 | 0.922 | 0.191 | 0.024 | 98.541 | 2.942 | 0.021 | 1.045 | 0.001 | 0.005 | 0.924 | 0.052 | 0.005 | 0.000 | 4.996 | 0.942 | 0.053 | 0.005 | | | | | |
| mid-Seg2 Kf-1 | 60.103 | 0.397 | 19.085 | 0.003 | 0.000 | 2.876 | 12.346 | 0.595 | 0.013 | 95.418 | 2.903 | 0.016 | 1.086 | 0.000 | 0.000 | 0.269 | 0.761 | 0.018 | 0.000 | 5.054 | 0.261 | 0.739 | 0.000 | 527.36 | 523.90 | 527.36 | 526.21 | |
| mid-Seg2 Kf-1 | 59.083 | 0.416 | 19.180 | 0.000 | 0.024 | 2.880 | 12.306 | 0.589 | 0.000 | 94.478 | 2.885 | 0.017 | 1.104 | 0.000 | 0.001 | 0.273 | 0.767 | 0.018 | 0.000 | 5.066 | 0.262 | 0.737 | 0.001 | 550.04 | 534.49 | 542.32 | 542.28 | |
| mid-Seg2 PI-2 | 64.349 | 0.748 | 20.168 | 0.016 | 0.140 | 10.284 | 1.468 | 0.298 | 0.014 | 97.485 | 2.907 | 0.029 | 1.074 | 0.001 | 0.007 | 0.901 | 0.085 | 0.009 | 0.000 | 5.011 | 0.908 | 0.085 | 0.007 | 522.44 | 527.74 | 522.44 | Failed | Avg = 524.2 |
| mid-Seg2 Kf-2 | 59.763 | 0.593 | 19.438 | 0.012 | 0.004 | 2.713 | 12.510 | 0.612 | 0.000 | 95.644 | 2.881 | 0.024 | 1.104 | 0.000 | 0.000 | 0.254 | 0.769 | 0.019 | 0.000 | 5.052 | 0.248 | 0.752 | 0.000 | | | | | |
| Middle of Segment-3 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| mid-Seg3 PI-1 | 63.330 | 0.591 | 20.030 | 0.040 | 0.334 | 10.530 | 0.738 | 0.238 | 0.004 | 95.835 | 2.904 | 0.023 | 1.082 | 0.002 | 0.016 | 0.936 | 0.043 | 0.007 | 0.000 | 5.014 | 0.940 | 0.043 | 0.016 | 546.32 | 522.45 | 546.32 | 538.37 | |
| mid-Seg3 Kf-1 | 59.164 | 0.477 | 18.927 | 0.021 | 0.031 | 2.871 | 12.219 | 0.380 | 0.000 | 94.089 | 2.894 | 0.020 | 1.091 | 0.001 | 0.002 | 0.272 | 0.762 | 0.012 | 0.000 | 5.054 | 0.263 | 0.736 | 0.002 | | | | | |
| mid-Seg3 PI-2 | 64.450 | 0.392 | 20.274 | 0.033 | 0.221 | 10.378 | 1.109 | 0.266 | 0.014 | 97.137 | 2.918 | 0.015 | 1.082 | 0.001 | 0.011 | 0.911 | 0.064 | 0.008 | 0.000 | 5.010 | 0.924 | 0.065 | 0.011 | 585.66 | 580.63 | 585.66 | 583.98 | uncertainty used: 0.03 |
| mid-Seg3 Kf-2 | 58.374 | 0.592 | 20.025 | 0.040 | 0.048 | 3.490 | 11.504 | 0.281 | 0.016 | 94.369 | 2.842 | 0.024 | 1.149 | 0.002 | 0.002 | 0.329 | 0.715 | 0.009 | 0.000 | 5.073 | 0.315 | 0.683 | 0.002 | | | | | |
| mid-Seg3 PI-3u | 63.667 | 0.505 | 20.201 | 0.014 | 0.344 | 10.712 | 0.713 | 0.260 | 0.000 | 96.416 | 2.904 | 0.019 | 1.086 | 0.001 | 0.017 | 0.947 | 0.041 | 0.008 | 0.000 | 5.022 | 0.942 | 0.041 | 0.017 | | | | | |
| mid-Seg3 Kf-3u | 58.341 | 0.499 | 19.420 | 0.015 | 0.011 | 3.122 | 12.000 | 0.520 | 0.000 | 93.930 | 2.864 | 0.021 | 1.124 | 0.001 | 0.001 | 0.297 | 0.752 | 0.016 | 0.000 | 5.075 | 0.283 | 0.716 | 0.001 | 554.67 | 525.31 | 554.67 | 544.88 | |
| mid-Seg3 Kf-3u | 59.449 | 0.500 | 19.170 | 0.036 | 0.000 | 3.053 | 12.198 | 0.365 | 0.023 | 94.795 | 2.887 | 0.021 | 1.097 | 0.001 | 0.000 | 0.287 | 0.756 | 0.011 | 0.000 | 5.061 | 0.276 | 0.724 | 0.000 | 541.77 | 520.61 | 541.77 | 534.72 | |
| Middle of Segment-4 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| mid-Seg4u PI-1 | 65.753 | 0.446 | 20.011 | 0.004 | 0.146 | 10.279 | 1.164 | 0.231 | 0.017 | 98.049 | 2.942 | 0.017 | 1.055 | 0.000 | 0.007 | 0.892 | 0.066 | 0.007 | 0.000 | 4.987 | 0.924 | 0.069 | 0.007 | 531.20 | 531.20 | 531.20 | Failed | avg = 531.20 |
| mid-Seg4u Kf-1 | 59.834 | 0.448 | 19.532 | 0.014 | 0.000 | 2.868 | 12.308 | 0.430 | 0.004 | 95.438 | 2.885 | 0.018 | 1.110 | 0.001 | 0.000 | 0.268 | 0.757 | 0.013 | 0.000 | 5.052 | 0.262 | 0.738 | 0.000 | | | | | |
| mid-Seg4u PI-2 | 62.188 | 0.598 | 20.888 | 0.017 | 0.200 | 10.466 | 1.133 | 0.286 | 0.000 | 95.776 | 2.863 | 0.023 | 1.133 | 0.001 | 0.010 | 0.934 | 0.067 | 0.008 | 0.000 | 5.040 | 0.924 | 0.066 | 0.010 | | | | | |
| mid-Seg4u Kf-2 | 58.976 | 0.573 | 19.612 | 0.026 | 0.000 | 2.774 | 12.464 | 0.347 | 0.022 | 94.794 | 2.866 | 0.024 | 1.123 | 0.001 | 0.000 | 0.261 | 0.773 | 0.011 | 0.000 | 5.060 | 0.253 | 0.747 | 0.000 | 525.12 | 525.12 | 525.12 | Failed | avg=525.15 |
| mid-Seg4u Kf-2 | 59.130 | 0.608 | 19.238 | 0.014 | 0.002 | 2.774 | 12.411 | 0.506 | 0.000 | 94.683 | 2.878 | 0.025 | 1.104 | 0.001 | 0.000 | 0.262 | 0.771 | 0.016 | 0.000 | 5.056 | 0.254 | 0.746 | 0.000 | 515.30 | 514.49 | 514.49 | 514.76 | |
| mid-Seg4l PI-3 | 64.029 | 0.522 | 20.246 | 0.003 | 0.139 | 10.479 | 0.688 | 0.356 | 0.030 | 96.492 | 2.913 | 0.020 | 1.086 | 0.000 | 0.007 | 0.924 | 0.040 | 0.010 | 0.001 | 5.001 | 0.952 | 0.041 | 0.007 | 537.26 | 513.68 | 537.26 | Failed | avg=529.40 |
| mid-Seg4l Kf-3 | 61.012 | 0.535 | 19.920 | 0.011 | 0.026 | 2.929 | 12.269 | 0.453 | 0.026 | 97.180 | 2.884 | 0.021 | 1.110 | 0.000 | 0.001 | 0.268 | 0.740 | 0.014 | 0.001 | 5.040 | 0.266 | 0.733 | 0.001 | | | | | |
| mid-Seg4l PI-4 | 65.286 | 0.572 | 20.542 | 0.011 | 0.106 | 10.419 | 1.151 | 0.187 | 0.004 | 98.278 | 2.916 | 0.022 | 1.081 | 0.000 | 0.005 | 0.902 | 0.066 | 0.005 | 0.000 | 4.998 | 0.927 | 0.067 | 0.005 | 522.23 | 522.23 | 522.23 | 522.23 | |
| mid-Seg4l Kf-4 | 59.957 | 0.495 | 19.522 | 0.023 | 0.000 | 2.794 | 12.501 | 0.544 | 0.031 | 95.865 | 2.883 | 0.020 | 1.106 | 0.001 | 0.000 | 0.260 | 0.767 | 0.017 | 0.001 | 5.056 | 0.254 | 0.746 | 0.000 | | | | | |
| Day-2 (01/25/17) | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Middle of Segment-5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| M246-midSeg-5L PI-1 | 67.000 | 0.513 | 19.510 | 0.000 | 0.223 | 11.695 | 0.945 | 0.227 | 0.045 | 100.158 | 2.948 | 0.019 | 1.012 | 0.000 | 0.011 | 0.998 | 0.053 | 0.006 | 0.001 | 5.047 | 0.940 | 0.050 | 0.010 | 584.45 | 534.69 | 584.46 | Failed | avg=567.87 |
| M246-midSeg-5L Kf-1 | 64.743 | 0.505 | 18.345 | 0.027 | 0.015 | 3.861 | 10.959 | 0.353 | 0.000 | 98.809 | 2.979 | 0.020 | 0.995 | 0.001 | 0.001 | 0.344 | 0.643 | 0.010 | 0.000 | 4.993 | 0.348 | 0.651 | 0.001 | | | | | |
| M246-midSeg-5L PI-2 | 68.070 | 0.473 | 19.057 | 0.013 | 0.326 | 11. | | | | | | | | | | | | | | | | | | | | | | |

American Mineralogist: November 2023 Online Materials AM-23-118674
 London: Macusani obsidian

| EMPA of feldspar pairs, MAC-246: 01/24/17-01/25/17 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|------------------|-------------------------------|--------------------------------|-------|-------|-------------------|------------------|-------------------|-------------------|---------|--------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|----------------|-------|-------|--------------------------|--------|--------|----------|------------------------|
| 15 kV, 10 nA, 2µm spot | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| SAMPLE | Weight Percent | | | | | | | | | | Atoms per 8 Oxygen | | | | | | | | | | Mole fractions | | | 2-Fsp T (Elkins & Grove) | | | | Comment |
| | SiO ₂ | P ₂ O ₅ | Al ₂ O ₃ | FeO | CaO | Na ₂ O | K ₂ O | Rb ₂ O | Cs ₂ O | TOTAL | Si | P | Al | Fe | Ca | Na | K | Rb | Cs | Sum | xAb | xOr | xAn | T-Ab | T-Or | T-An | T-Convrg | |
| Middle of Segment-6 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| M246-midSeg-6L PI-1 | 65.980 | 0.614 | 19.831 | 0.031 | 0.469 | 11.526 | 0.919 | 0.225 | 0.005 | 99.600 | 2.921 | 0.023 | 1.035 | 0.001 | 0.022 | 0.989 | 0.052 | 0.006 | 0.000 | 5.051 | 0.930 | 0.049 | 0.021 | 616.71 | 550.93 | 616.71 | 594.78 | |
| M246-midSeg-6L Kf-1 | 64.745 | 0.567 | 18.399 | 0.028 | 0.035 | 4.454 | 9.997 | 0.414 | 0.000 | 98.639 | 2.975 | 0.022 | 0.996 | 0.001 | 0.002 | 0.397 | 0.586 | 0.012 | 0.000 | 4.991 | 0.403 | 0.595 | 0.002 | | | | | |
| M246-midSeg-6L PI-2 | 67.307 | 0.352 | 19.655 | 0.046 | 0.334 | 11.680 | 0.933 | 0.287 | 0.009 | 100.604 | 2.950 | 0.013 | 1.015 | 0.002 | 0.016 | 0.993 | 0.052 | 0.008 | 0.000 | 5.049 | 0.936 | 0.049 | 0.015 | 631.38 | 538.78 | 631.38 | 600.52 | |
| M246-midSeg-6L Kf-2 | 63.028 | 0.477 | 18.993 | 0.054 | 0.152 | 4.776 | 9.885 | 0.345 | 0.006 | 97.715 | 2.933 | 0.019 | 1.042 | 0.002 | 0.008 | 0.431 | 0.587 | 0.010 | 0.000 | 5.032 | 0.420 | 0.572 | 0.007 | | | | | |
| M246-midSeg-6U PI-3 | 68.112 | 0.498 | 19.498 | 0.048 | 0.542 | 11.422 | 0.815 | 0.286 | 0.008 | 101.228 | 2.961 | 0.018 | 0.999 | 0.002 | 0.025 | 0.963 | 0.045 | 0.008 | 0.000 | 5.021 | 0.932 | 0.044 | 0.024 | 612.07 | 546.71 | 612.05 | 590.28 | |
| M246-midSeg-6U PKf3 | 63.875 | 0.492 | 18.263 | 0.016 | 0.078 | 4.425 | 10.061 | 0.293 | 0.002 | 97.504 | 2.971 | 0.019 | 1.001 | 0.001 | 0.004 | 0.399 | 0.597 | 0.009 | 0.000 | 5.001 | 0.399 | 0.597 | 0.004 | | | | | |
| Middle of Segment-7 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| M246-midSeg-7L PI-1 | 69.642 | 0.379 | 20.215 | 0.062 | 0.413 | 11.266 | 0.797 | 0.298 | 0.005 | 103.077 | 2.966 | 0.014 | 1.015 | 0.002 | 0.019 | 0.930 | 0.043 | 0.008 | 0.000 | 4.997 | 0.937 | 0.044 | 0.019 | 588.59 | 538.14 | 588.58 | 571.78 | |
| M246-midSeg-7L Kf-1 | 65.017 | 0.436 | 18.934 | 0.043 | 0.016 | 3.869 | 10.817 | 0.350 | 0.000 | 99.484 | 2.968 | 0.017 | 1.019 | 0.002 | 0.001 | 0.342 | 0.630 | 0.010 | 0.000 | 4.989 | 0.352 | 0.647 | 0.001 | | | | | |
| M246-midSeg-7L PI-2 | 70.018 | 0.522 | 19.947 | 0.022 | 0.418 | 11.256 | 1.096 | 0.237 | 0.009 | 103.525 | 2.971 | 0.019 | 0.997 | 0.001 | 0.019 | 0.926 | 0.059 | 0.006 | 0.000 | 4.998 | 0.922 | 0.059 | 0.019 | 593.76 | 549.70 | 593.76 | 579.07 | uncertainty used: 0.01 |
| M246-midSeg-7L Kf-2 | 65.327 | 0.299 | 18.764 | 0.041 | 0.026 | 3.854 | 10.715 | 0.317 | 0.000 | 99.343 | 2.983 | 0.012 | 1.010 | 0.002 | 0.001 | 0.341 | 0.624 | 0.009 | 0.000 | 4.982 | 0.353 | 0.646 | 0.001 | | | | | |
| M246-midSeg-7U PI-3 | 69.097 | 0.358 | 19.977 | 0.007 | 0.419 | 11.436 | 1.053 | 0.197 | 0.001 | 102.544 | 2.963 | 0.013 | 1.010 | 0.000 | 0.019 | 0.951 | 0.058 | 0.005 | 0.000 | 5.019 | 0.925 | 0.056 | 0.019 | 605.92 | 554.17 | 605.92 | 588.67 | |
| M246-midSeg-7U Kf-3 | 64.114 | 0.480 | 19.059 | 0.064 | 0.045 | 4.264 | 10.498 | 0.280 | 0.000 | 98.805 | 2.948 | 0.019 | 1.033 | 0.002 | 0.002 | 0.380 | 0.616 | 0.008 | 0.000 | 5.009 | 0.381 | 0.617 | 0.002 | | | | | |
| M246-midSeg-7U PI-4 | 70.025 | 0.508 | 19.999 | 0.058 | 0.409 | 11.047 | 1.030 | 0.224 | 0.000 | 103.300 | 2.973 | 0.018 | 1.001 | 0.002 | 0.019 | 0.909 | 0.056 | 0.006 | 0.000 | 4.985 | 0.924 | 0.057 | 0.019 | 644.05 | 556.13 | 644.05 | 614.74 | |
| M246-midSeg-7U Kf-4 | 64.892 | 0.536 | 19.037 | 0.033 | 0.205 | 5.697 | 8.430 | 0.369 | 0.000 | 99.199 | 2.952 | 0.021 | 1.021 | 0.001 | 0.010 | 0.503 | 0.489 | 0.011 | 0.000 | 5.008 | 0.502 | 0.488 | 0.010 | | | | | |
| Hot End (segment-8) | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| M246-Seg-8 PI-1 | 68.860 | 0.186 | 20.102 | 0.066 | 0.756 | 11.702 | 0.540 | 0.258 | 0.000 | 102.470 | 2.957 | 0.007 | 1.017 | 0.002 | 0.035 | 0.974 | 0.030 | 0.007 | 0.000 | 5.030 | 0.938 | 0.028 | 0.033 | 606.74 | 515.02 | 606.74 | 576.17 | |
| M246-Seg-8 Kf-1 | 65.266 | 0.364 | 19.126 | 0.087 | 0.049 | 4.517 | 10.395 | 0.229 | 0.012 | 100.045 | 2.961 | 0.014 | 1.023 | 0.003 | 0.002 | 0.397 | 0.602 | 0.007 | 0.000 | 5.009 | 0.397 | 0.601 | 0.002 | | | | | |
| Middle of Segment-4 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| M246-midSeg-4U PI-4 | 68.322 | 0.433 | 19.604 | 0.000 | 0.225 | 11.141 | 1.626 | 0.162 | 0.000 | 101.512 | 2.965 | 0.016 | 1.003 | 0.000 | 0.010 | 0.937 | 0.090 | 0.005 | 0.000 | 5.026 | 0.903 | 0.087 | 0.010 | 566.79 | 566.79 | 566.79 | 566.79 | |
| M246-midSeg-4U Kf-4 | 64.340 | 0.523 | 18.364 | 0.014 | 0.009 | 3.399 | 11.373 | 0.345 | 0.001 | 98.367 | 2.976 | 0.020 | 1.001 | 0.001 | 0.000 | 0.305 | 0.671 | 0.010 | 0.000 | 4.985 | 0.312 | 0.687 | 0.000 | | | | | |
| M246-midSeg-4L PI-5 | 67.299 | 0.523 | 20.016 | 0.048 | 0.161 | 11.464 | 0.876 | 0.266 | 0.002 | 100.656 | 2.941 | 0.019 | 1.031 | 0.002 | 0.008 | 0.971 | 0.049 | 0.007 | 0.000 | 5.028 | 0.945 | 0.048 | 0.007 | 549.19 | 519.52 | 519.52 | 529.41 | |
| M246-midSeg-4L Kf-5 | 63.466 | 0.449 | 18.725 | 0.000 | 0.000 | 3.180 | 11.598 | 0.357 | 0.037 | 97.812 | 2.959 | 0.018 | 1.029 | 0.000 | 0.000 | 0.287 | 0.690 | 0.011 | 0.001 | 4.994 | 0.294 | 0.706 | 0.000 | | | | | |
| Middle of Segment-3 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| M246-midSeg-3L PI-4 | 68.630 | 0.573 | 19.853 | 0.030 | 0.285 | 11.800 | 0.905 | 0.340 | 0.000 | 102.416 | 2.951 | 0.021 | 1.006 | 0.001 | 0.013 | 0.984 | 0.050 | 0.009 | 0.000 | 5.036 | 0.940 | 0.047 | 0.013 | 557.53 | 529.17 | 557.53 | 548.08 | |
| M246-midSeg-3L Kf-4 | 63.236 | 0.516 | 18.741 | 0.007 | 0.000 | 3.295 | 11.709 | 0.414 | 0.009 | 97.928 | 2.950 | 0.020 | 1.030 | 0.000 | 0.000 | 0.298 | 0.697 | 0.012 | 0.000 | 5.008 | 0.300 | 0.700 | 0.000 | | | | | |
| M246-midSeg-3L PI-5 | 67.480 | 0.606 | 19.978 | 0.013 | 0.347 | 11.337 | 0.899 | 0.251 | 0.000 | 100.913 | 2.940 | 0.022 | 1.026 | 0.000 | 0.016 | 0.958 | 0.050 | 0.007 | 0.000 | 5.020 | 0.935 | 0.049 | 0.016 | 545.12 | 504.84 | 504.84 | 518.26 | |
| M246-midSeg-3L Kf-5 | 62.817 | 0.465 | 18.570 | 0.004 | 0.023 | 3.183 | 11.687 | 0.418 | 0.014 | 97.182 | 2.953 | 0.019 | 1.029 | 0.000 | 0.001 | 0.290 | 0.701 | 0.013 | 0.000 | 5.006 | 0.292 | 0.706 | 0.001 | | | | | |
| Middle of Segment-2 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| M246-midSeg-2L PI-5 | 69.412 | 0.567 | 19.289 | 0.010 | 0.074 | 11.856 | 0.722 | 0.234 | 0.015 | 102.180 | 2.982 | 0.021 | 0.977 | 0.000 | 0.003 | 0.987 | 0.040 | 0.006 | 0.000 | 5.016 | 0.958 | 0.038 | 0.003 | 545.12 | 504.84 | 504.84 | 518.26 | |
| M246-midSeg-2L Kf-5 | 63.753 | 0.507 | 18.963 | 0.034 | 0.000 | 3.159 | 11.568 | 0.540 | 0.000 | 98.523 | 2.952 | 0.020 | 1.035 | 0.001 | 0.000 | 0.284 | 0.683 | 0.016 | 0.000 | 4.992 | 0.293 | 0.707 | 0.000 | | | | | |
| M246-midSeg-2L PI-6 | 66.429 | 0.492 | 19.539 | 0.030 | 0.062 | 11.401 | 1.107 | 0.250 | 0.000 | 99.310 | 2.946 | 0.018 | 1.021 | 0.001 | 0.003 | 0.980 | 0.063 | 0.007 | 0.000 | 5.040 | 0.937 | 0.060 | 0.003 | 561.29 | 531.46 | 561.29 | Failed | Avg=551.35 |
| M246-midSeg-2L Kf-6 | 62.803 | 0.484 | 18.255 | 0.034 | 0.010 | 3.260 | 11.416 | 0.513 | 0.012 | 96.787 | 2.963 | 0.019 | 1.015 | 0.001 | 0.001 | 0.298 | 0.687 | 0.016 | 0.000 | 5.001 | 0.302 | 0.697 | 0.001 | | | | | |
| Middle of Segment-1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| M246-midSeg-1L PI-5 | 67.621 | 0.540 | 19.552 | 0.033 | 0.080 | 11.766 | 0.594 | 0.251 | 0.017 | 100.454 | 2.957 | 0.020 | 1.008 | 0.001 | 0.004 | 0.998 | 0.033 | 0.007 | 0.000 | 5.028 | 0.964 | 0.032 | 0.004 | | | | | |
| M246-midSeg-1L Kf-5 | 61.955 | 0.529 | 18.634 | 0.049 | 0.000 | 2.914 | 12.212 | 0.535 | 0.035 | 96.862 | 2.936 | 0.021 | 1.041 | 0.002 | 0.000 | 0.268 | 0.738 | 0.016 | 0.001 | 5.023 | 0.266 | 0.734 | 0.000 | 526.77 | 491.45 | 526.77 | 514.99 | |
| M246-midSeg-1L Kf-6 | 62.567 | 0.582 | 18.721 | 0.005 | 0.000 | 2.965 | 11.872 | 0.661 | 0.017 | 97.391 | 2.942 | 0.023 | 1.038 | 0.000 | 0.000 | 0.270 | 0.712 | 0.020 | 0.000 | 5.006 | 0.275 | 0.725 | 0.000 | 532.13 | 492.43 | 527.07 | 517.21 | |
| M246-midSeg-1U PI-6 | 66.542 | 0.540 | 19.613 | 0.001 | 0.087 | 11.639 | 0.759 | 0.214 | 0.000 | 99.396 | 2.944 | 0.020 | 1.023 | 0.000 | 0.004 | 0.998 | 0.043 | 0.006 | 0.000 | 5.038 | 0.955 | 0.041 | 0.004 | 536.38 | 508.54 | 536.37 | 527.10 | |
| M246-midSeg-1U Kf-6 | 63.179 | 0.414 | 18.540 | 0.000 | 0.000 | 2.951 | 11.621 | 0.468 | 0.012 | 97.185 | 2.966 | 0.016 | 1.026 | 0.000 | 0.000 | 0.269 | 0.696 | 0.014 | 0.000 | 4.986 | 0.278 | 0.722 | 0.000 | | | | | |
| Cold End (edge of segment-1) | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| M246-ColdEnd PI-5 | 66.336 | 0.780 | 19.868 | 0.000 | 0.074 | 11.700 | 0.818 | 0.215 | 0.000 | 99.791 | 2.925 | 0.029 | 1.032 | 0.000 | 0.003 | 1.000 | 0.046 | 0.006 | 0.000 | 5.042 | 0.953 | 0.044 | 0.003 | 515.57 | 507.89 | 515.57 | 513.01 | |

| EMPA of feldspar pairs, MAC-246: 01/24/17-01/25/17 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|------------------|-------------------------------|--------------------------------|-------|-------|-------------------|------------------|-------------------|-------------------|--------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|----------------|-------|-------|--------------------------|------|------|------|----------|---------|
| 15 kV, 10 nA, 2µm spot | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Weight Percent | | | | | | | | | | Atoms per 8 Oxygen | | | | | | | | | | Mole fractions | | | 2-Fsp T (Elkins & Grove) | | | | | Comment |
| SAMPLE | SiO ₂ | P ₂ O ₅ | Al ₂ O ₃ | FeO | CaO | Na ₂ O | K ₂ O | Rb ₂ O | Cs ₂ O | TOTAL | Si | P | Al | Fe | Ca | Na | K | Rb | Cs | Sum | xAb | xOr | xAn | T-Ab | T-Or | T-An | T-Convrg | Comment |
| M246-ColdEnd Kf-S | 61.299 | 0.739 | 18.929 | 0.000 | 0.000 | 2.684 | 12.275 | 0.551 | 0.019 | 96.496 | 2.915 | 0.030 | 1.061 | 0.000 | 0.000 | 0.247 | 0.745 | 0.017 | 0.000 | 5.015 | 0.249 | 0.751 | 0.000 | | | | | |